

### **SPECIFICATIONS**

| Overall length                                  | 12,35 m     | 40'6''      |
|---|-------------|-------------|
| Overall Length with bowsprit                    | 12,95 m     | 42'5''      |
| Hull length                                     | 11,99 m     | 39'4''*     |
| Waterline length                                | 11,47 m     | 37'7"       |
| Beam  | 3,99 m      | 13'1"       |
| Displacement light load<br>with deep draft keel | 7 784 kg    | 17 161 lbs  |
| Standard keel draft                             | 2,25 m      | 7'4''       |
| Standard keel weight                            | 2 003 kg    | 4 416 lbs   |
| Shoal keel draft                                | 1,60 m      | 5'2''       |
| Shoal keel weight                               | 2 326 kg    | 5 128 lbs   |
| Lifting keel draft                              | 1,37-2,97 m | 4'5''-9'8'' |
| Lifting keel weight                             | 1 807 kg    | 3 984 lbs   |

| Fuel capacity  | 200 L                           | 53 US gal                                      |  |  |
|--|---------------------------------|--|--|--|
| Water capacity   | 530 L                           | 140 US gal                                     |  |  |
| Fridge capacity  | 190 L                           | 50 US gal                                      |  |  |
| Holding tank capacity  | 80 L                            | 21 US gal                                      |  |  |
| Standard mainsail horizontally-cut ir<br>High Strength polyester | 1 42,70 m <sup>2</sup>          | 459 Sq ft                                      |  |  |
| Furling 110 % genoa in High Strengtł<br>polyester                | genoa in High Strength 34,30 m² |  |  |  |
| CE category 2 cabins layout                                      | A6 / B7                         | / C9 / D9                                      |  |  |
| CE category 3 cabins layout                                      | A8 / B10                        | A6 / B7 / C9 / D9<br>A8 / B10 / C10 / D10      |  |  |
| Architect / Designer   | Piaton B                        | rrd Yacht Design<br>ercault & Co<br>eau Design |  |  |
|  | *Crook an osificatio            | ma 12 015 m / 70'5                             |  |  |

JEANNEAU SUN ODYSSEY





### AN EXCEPTIONAL LEVEL OF EQUIPMENT \_

#### EXTERIOR

#### Sailing features

- High aspect ratio rig
- Harken<sup>®</sup> roof and primary winches
- Harken® deck hardware
- · Anodized aluminium mast and boom • Boom with rigid boom vang and lowered gooseneck,
- to ease maneuvering · Semi-battened mainsail and furling genoa with
- UV protection
- Discontinuous standing rigging, stainless steel wire
- · Lazy bag and lazy jacks
- · Sheets lead back to the helm German sheeting
- · Large choice of sails sets and optional Performance mast

#### INTERIOR

- One-level interior with no door sills
- Leather-wrapped handrails
- LED lighting
- Large, rectangular double berths
- Fully-upholstered hull sides
- Blinds for each hatch and opening in the forward and aft cabins
- Numerous choices of interior ambiances
- Large seaworthy storage spaces, seaworthy with fiddles. Soft closing drawers and cabinets.
- Shower divider in heads

### TECHNICAL .

#### Electrical

- LED navigation and anchoring lights
- 12 V electrical panel
- Lead battery Exide Dual Marine
- 125 Ah alternator and charge distributor/isolator
- · Positive and negative battery cut-off switches to better protect battery banks

#### Construction

- Single skin hull, hand-laid fibreglass, ISO gelcoat surface, protective "barrier coat"
- Infused fiberglass inner liner, easy access to grounding frame, relamination in stays attachment areas
- Prisma Process® injected deck, ISO gelcoat surface, discontinuous balsa block coring - 30 % weight savings as compared to traditional decks
- Twin rudders with self-aligning roller bearings and textile lines, to increase control and pleasure in navigation
- Negative bow: allows to increase waterline length while
- improving the fineness of the water lines
- The bow rises out of the water: reduce submerged surface in light winds

#### Chart table

- · Large navigation desk with leatherette lining and interior storage for a portable computer, electrical panel and books storage
- Galley
- U-shape galley, ideally located near the centre of gravity of the boat
- Corian counter top
- Double stainless steel sinks
- 2-burner stove with oven
- Fridge 190 L / 50 US gal (with an optional front access)

#### Water System

- Hot and cold cockpit shower
- Hot water heater 40 L / 11 US gal
- "Heavy-duty" water pump

#### Cockpit

- GRP cockpit table
- · Leather-covered stainless steel steering wheels
- Large aft fold-down swim platform with telescopic ladder
- Telescopic bath scale
- Hinged companionway doors

#### Deck

- Flush deck hatches
- Long tinted acrylic roof windows
- External woodwork and inlays
- Mid-ship cleats

#### Sofa Lounge

- Convivial and comfortable sofa lounge
- Sliding seat
- Bar furniture with drawer

### Woodwork

- Woodwork in Alpi® Teak or grey Cedar
- UV stabilised varnish
- Ceruse light or dark Oak laminate floorboards
- Numerous solid wood or Alpi® mouldings

#### Engine

- Fixed 3-blade propeller
- · Sound insulation, with fire retardant film

# \*Greek specifications 12,015 m / 39'5'

### 

| TRIM LEVELS AND PACKS  | "PREMIERE" | "PREFERENCE" |
|--|------------|--------------|
| I TRIM LEVEL   |            |              |
|  |            |              |
| GRP bowsprit with integrated anchor roller (replaces the standard anchor roller) | ٠          | •            |
| Second windlass control with chain counter, installed in the cockpit             | •          | •            |
| Electric windlass  | •          | •            |
| GRP multifunction cockpit table (replaces standard cockpit table)                | •          | •            |
| Lifeline   | •          | •            |
| Power 220 V  | •          | •            |
| USB plugs (7)  | •          | •            |
| Navicolor battery monitoring   | •          | •            |
| 2 burner cooker and oven with grill function (replaces standard 2 burner cooker) | •          | •            |
| Additional service batteries (2 x 115 Ah / 12 V)                                 | •          | •            |
| 60 Ah battery charger  | •          | •            |
| Halyard bags in the cockpit (2)  |            | •            |
| Indirect LED lighting, and lamps on bulkheads                                    |            | •            |
| LED courtesy lighting in the cockpit   |            | •            |
| Upholstered bulkheads  |            | •            |
| Wine storage locker under floorboards (12 bottles)                               |            | •            |
| Signature clock and barometer set at the chart table                             |            | •            |
| Vertical door fridge   |            | •            |
| Shades for windows and ports in the saloon                                       |            | •            |

### EXTERIOR AND TECHNICAL EQUIPMENT

### **I** ARCHITECTURE

- Full-length chine for improved stability and speed · Long waterline for better speed while sailing and
- under power · L-shaped cast iron keel less exposed to seaweed
- and lines
- Twin rudders with self-aligning roller bearings and textile lines, to increase control and pleasure in navigation
- Negative bow: allows to increase waterline length while improving the fineness of the water lines
- The bow rises out of the water: reduce submerged surface in light winds

### SAILS

#### Standard

- Mainsail horizontally-cut in High Strength polyester, with UV protection
- Semi-battened mainsail with 2 reefs and UV protection 42,70 m² / 459 Sq ft
- 110 % furling genoa with UV protection 34,30 m² / 369 Sq ft

#### Options

- In mast furling main sail horizontally-cut in High
- Strength polyester, 35,10 m² / 378 Sq ft
- Self-tacking jib with UV protection in High Strength polyester 25,40 m² / 273 Sq ft
- Code 0 in CZ30 laminate for standard mast, 61,10 m<sup>2</sup> / 657 Sq ft, with continuous line furling gear (requires Downwind pack)
- Code 0 in CZ30 laminate for Performance mast, 69,40 m² / 747 Sq ft, with continuous line furling gear (requires Downwind pack)

### SAIL HANDLING

#### Standard

- Mainsheet attached to Dyneema® bridle forward of companionway, with sheets lead back to the cockpit winches
- Adjustable genoa sheet friction rings in cockpit
- Spinlock<sup>®</sup> jammers

- Coachroof winch 1 x Harken® 40.2 ST to port
- Genoa winches 2 x Harken® 46.2 ST winches for easy use at the helm stations
- Harken<sup>®</sup> winch handle

#### Options

- Self-tacking jib ball bearing track on coachroof
- Electrical coachroof winch Harken® 40.2 ST
- 2 x electrical primary winches Harken® 46.2 ST
- Extra Harken® 40.2 ST winch to starboard on coachroof (in Downwind pack)

## **I** MAST AND RIGGING

#### Standard

- Classic mast in anodised aluminium with double spreaders, deck-stepped
- Aluminium boom with rigid vang and lowered goose
- neck for easier handling
- Textile non adjustable backstay, with simple turnbuckle • Genoa furler with double slot, furling line lead aft to
- cockpit on coach roof
- Running rigging: topping lift, mainsail halyard, genoa halyard, mainsheet, genoa sheets... in polyester
- Standing rigging discontinuous 1 x 19 stainless steel wire • Genoa lead rings adjustable with 3D adjustment
- · Asymmetrical lazy bag with integrated lazy jacks

#### Option

- Furling mast aluminium with double spreaders, deckstepped
- Textile adjustable backstay with turnuckle for classic mast

### **I** COCKPIT

#### Standard

- Walk-in access to side decks, enabling to walk around the deck without crossing any steps.
- GRP cockpit table with foldable sides
- Teak inlay on bench seat and transom platform
- Coaming with ideal height for comfort and safety (33 cm / 13")
- · Cockpit lockers: 1 impermeable on starboard side, 1 drained on port side (versions C and D only), 1 large

locker on the cockpit floor, 1 liferaft locker with open access to transom platform 92 x 60 x 42 cm / 3' x 2' x 1'4''

- Universal gas box, cut-off valve under the stove
- Wheels with leather wrap, space for flush mounted GPS at each helm, stainless steel handrail
- Emergency tiller, and fitting in cockpit floor
- Engine control: throttle lever at starboard helmstation and oriented engine panel on the cockpit table
- Large bathing platform 0,76 x 2,30 m / 2'5" x 7'6" with telescopic ladder
- · Hinged companionway doors in plexiglass
- Sliding horizontal hatch in plexiglass

#### Options

- Multifunctions GRP cockpit table with foldable sides, with stainless steel handrails, central storage, cup holders, bottle storage, protective handrail, lighting, 12 V plug et optional portable fridge (included in "PREMIERE" and "PREFERENCE" Trim Level)
- Solid wood cockpit table with the same functions as the multifunctional polyester table, but with folding sides and solid wood central surface
- Large cockpit sprayhood, Sunbrella®, high
- transparency windscreen and LED cockpit lighting · Cockpit bimini with stainless steel bows in
- Sunbrella®, foldable with storage cover
- Cockpit enclosure kit in Sunbrella®, fitted on the sprayhood and bimini
- Electrical bathing platform system with remote

### **I** DECK HARDWARE

### Standard

- Bow pulpit in stainless steel
- Stern pushpits in stainless steel with buoy bracket and emergency ladder
- Double level of stainless steel lifelines
- 6 aluminium mooring cleats
- Stainless steel handrails on coachroof (2)
- Deep anchor locker
- Long fixed tinted windows along coachroof
- Coachroof windows in the aft cabins (2)

#### DOWNWIND PACK

- Spinnaker rigging with Spinlock® jammer
- Halyards and sheet for asymetrical spinnaker / Code 0 (2 polyester halyards, 1 sheet and 1 tack line in Dyneema®,
- pulleys on mast step and side decks)
- Extra Harken® 40.2 ST winch to starboard on coachroof • Extra winch handle
- Windex 15" on mast head

#### PERFORMANCE PACK

#### Downwind pack

- Tall anodised mast with 2 spreader, cathedral geometry
- Dyform standing rigging
- Performance full-batten mainsail, in DCX® grey,
- 2 automatic reefs 43,80 m² / 471 Sq ft
- 110 % Performance genoa, in DCX  $^{\odot}$  grey, with Sunbrella  $^{\odot}$  UV protection and stainless steel eyelets 35,90 m² / 386 Sq ft
- Dyneema® low-stretch halyards and sheets for main and genoa
- Hydraulic textile adjustable backstay
- Composite steering wheels lighter than stainless steering wheels
- Lazy bag Performance
- FlatDeck genoa furler

#### VOYAGER PACK

- High transparency sprayhood with LED lighting Sunbrella®
- Outboard engine bracket
- Releasable forestay + deck fittings
- Solar panel on coachroof with charging relay
- Seawater / freshwater foot pump in the galley
- Stainless steel davit arch

#### ENTERTAINMENT PACK AUDIO

- RA70N Fusion audio player (Radio / USB / Bluetooth...) at chart table
- Pioneer<sup>®</sup> speakers in the saloon
- Speakers in the cockpit

#### ENTERTAINMENT PACK VIDEO

- RA70N Fusion audio player (Radio / USB / Bluetooth...) at chart table
- Pioneer<sup>®</sup> speakers in the saloon
- Waterproof speakers in the cockpit
- TV prefit in the saloon

**ENGINE** 

Alternator 125 Ah

exhaust fitting

from aft cabins

Options

• Fixed 3 blade propeller

• Yanmar Engine 3JH5E Shaft Drive - 40 HP / 29 kW -

on the cockpit table. Throttle at the starboard helm

• Engine panel oriented toward helmsman, located

• Built-in muffler, air ventilation and stainless steel

• Ventilation system extractor fan located near the

room. Outlets vents at the back of cockpit

engine, benefiting from the insulation of the engine

• Roto moulded fuel tank (200 L / 53 US gal) located

under the aft cabin berth, fuel / water separator

· Access behind steps to engine compartment and

• Yanmar Engine 4JH45 Common Rail Shaft Drive - 45

• Retractable bow thruster 4,3 kW 85 kgf (187,4 lbs)

• Insulation: foam, with fire retardant film

Standard

station

 $\boldsymbol{\cdot}$  TV antenna for mast fitting

#### • Large, fixed hull ports (8)

- Opening ports in the roof (2)
- Opening deck flush hatches (4)
- Opening ports towards cockpit in the aft cabins (1 per cabin)
- Opening ports towards side-deck in the aft cabins (1 per cabin)

#### Options

- Folding pulpits seating
- Lifeline gates
- Rubrail for hull protection
- Mooring kit: 6 fenders and 4 docklines
- Anchoring kit with Delta 20 kg / 44 lbs, 32 m / 104' of 10 mm chain and 45 m / 147' line

#### LIGHTING

#### Standard

• Full LED interior lighting

#### **|** ELECTRICAL

#### Standard

- Main 12 V electrical panel at the chart table
- 12 V Circuit for house and engine system
- Domestic battery bank capacity 2 x 115 Ah / 12 V
- Engine start battery capacity 1 x 110 Ah / 12 V
- 12 V engine alternator: 125 Ah
- $\bullet$  Positive and negative battery switch 12 V in the aft cabin

#### Options

- Lithium domestic battery bank 2 x 90 Ah / 12 V
- USB plug in each cabin
- $\cdot$  Inverter 12 V > 220 V 2 000 W enable to use 220 V appliance from the domestic battery bank
  - sphance from the domestic battery bank

#### **I** PLUMBING

### Standard

### FRESH WATER

- Hot and cold pressurized water circuit with semi-rigid plastic pipes
- "Heavy-duty" water pump (19 L / 5 US gal / mn),
- accumulator tank for consistent water pressure • Water roto moulded tank: 330 L / 87 US gal, under
- the forward cabin berth
- Water roto moulded tank: 200 L / 53 US gal, under the starboard aft cabin berth
- Tank gauges (1 per tank)
- Tank manifold with selector valves
- Water boiler 40 L / 11 US gal connected to the engine and 220 V circuit
- · Hot and cold cockpit shower on transom

#### GREY AND BLACK WATER

- Electrical shower pumps, self-activating
- Large marine toilets with hand pump
- Black water tank 80 L / 21 US gal, with gravity drain and deck fitting (versions A and B)
- $\cdot$  Black water tank 130 L / 34 US gal, with gravity drain and deck fitting (versions C and D)

#### **BILGES DRAINAGE**

- Electric bilge pump located in bilge area with activation via switch at electrical panel
- Dual-action manual bilge pump located in the
- cockpit, with separate hose from primary bilge pump

#### GAS

- Gas leakage detector
- Options
- Electric Quiet-Flush toilets, on fresh water circuit, in place of manual toilets
- Water intake in the cockpit. Enable to connect the fresh water circuit directly to the shore

HP / 33 kW - Alternator 125 Ah

with a dedicated 12 V battery bank

• Flex-o-Fold 3 blade folding propeller

### INTERIOR EQUIPMENT AND LAYOUTS

#### keelboat version



Version **A** Forward Owner's cabin 1 aft cabin / 1 head Sink-dressing in forward cabin, optional

#### **WOODWORK**

#### Standard

• Alpi® Teck interior woodwork laminated with solid wood

- trim, UV stabilized varnish
- · Fully-upholstered hull sides and ceiling
- Light ceruse Oak laminate floorboards

#### Options

- · Woodwork in Alpi<sup>®</sup> grey Cedar mat finish, open-pore varnish
- Dark Oak laminate floorboards

#### SALOON

#### Standard

- · Comfortable seating arrangement to starboard with view of sea though hull ports
- · Hinged storage compartments under settee
- Large storage behind backrests
- · Large table with 2 removable aluminium legs
- Convertible berth in saloon

#### Option

• "Luxe" folding table on telescopic legs

#### SOFA LOUNGE

- Comfortable sofa lounge at the centre of gravity of the boat
- · Sliding seat, for more comfort, bringing additional seating around the table
- Bar furniture with drawe
- Numerous and voluminous storage spaces

#### **|** CHART TABLE

- · Large chart table with leatherette worktop opening compartment, for laptop computer
- Book shelve
- Multiple storage for telephone, keys...
- Large storage space under electrical panel for books and other navigation equipment, storage underneath the seat
- · Access to central cabinet storage compartment
- Bicolour reading light
- · Ergonomic seat, seaworthy



GALLEY

· Corian counter top, with fiddles

· Large drawer in the centre cabinet

· Soft-close, fully-extending drawers

• 2 burner stove with protective handrail

• Open storage behind the galley

• Opening hatch above the stove

• High Density mattresses in cabins

cabin and head (All versions)

• Waste bin 26 L / 7 US gal

**COMFORT** 

Standard

Options

Standard

Version B Forward Owner's cabin. 1 aft cabin / 2 heads



Version C Forward Owner's cabin. 2 aft cabins / 1 head Dressing + furniture with private sink in forward cabin, in option



Version D Forward Owner's cabin. 2 aft cabins / 2 heads

#### AFT CABIN(S)

- Large domestic size, berth 2,02 x 1,38/1,22 m / 6'7" x 4'6"/4'
- Hanging locker storage shelf along hull
- LED Lighting
- LED reading lights
- 1 long fixed hull port, 1 large fixed cockpit window • 1 opening port towards the cockpit, 1 opening port
- towards the side decks
- · Blinds for each opening
- · Access to tanks and technical area between the cabins
- Aft head: double access, from starboard cabin and saloon, GRP sink furniture, storage with towel shelf, base cabinet, wall cabinet with 2 mirrors, large roof window, opening port for light and large roof window, opening port for light and ventilation, indirect LED lighting, shower, shower drain with automatic switch, water inlet valve and connector underneath the sink, large marine toilet with manual pump, hook, large mirror, shower separated with a plexiglass door

#### WORKSHOP ON PORT SIDE (versions A and B)

#### Standard

- · Sail locker located on port side behind the chart table, double access from the interior and the cockpit
- LED lighting
- Large fixed hull window
- Access to the tank
- · Direct access to electrical panels
- Lateral storage locker

- Extra fridge drawer in the sail locker 75 L / 20 US gal
- Extra freezer in the sail locker 75 L / 20 US gal

compartment with direct access from the cabin, GRP sink furniture, base cabinet, storage with towel shelf, large deck hatch, for light and ventilation, indirect LED lighting, shower, shower drain with automatic switch, water inlet valve and connector underneath the sink, large marine toilet with manual pump, hook, shower separated with a plexiglass door

- with private sink (versions A and C)
- · Electric Quiet-Flush toilets, on seawater circuit, in place

# HEADROOM

| Forward cabin | 1,87 m | 6'1"  | Companionway | 1,87 m | 6'1'' | Galley   | 1,91 m | 6'3" | Forward head | 1,85 m | 6'0'' |
|---------------|--------|-------|--------------|--------|-------|----------|--------|------|--------------|--------|-------|
| Aft cabin(s)  | 1,90 m | 6'2'' | Saloon       | 1,98 m | 6'5"  | Aft head | 1,93 m | 6'3" | Sprayhood    | 1,84 m | 6'0'' |



- Options

reserve the right to modify equipment or specification without advance tractual and we no c nent is r 191 372 702 RCS La Roche sur Yon. Simplified inventory. This doci

Updated June 2022. MORGANE - Les Herbiers

notice.

Pushed air heating system 5 500 W with outlets in each

FORWARD OWNER'S CABIN Standard

• Large domestic size, rectangular berth, 2,00 x 1,50 m / 6'6" x 4'11"

• U-shape galley located on port side, with view on the sea

• Double stainless steel sinks with chrome fixtures. Sink

• Fridge 190 L / 50 US gal (with optional front opening)

• Cushions in High Density foam 130 mm in the saloon

cover and anti projection board, in Corian

- · Large hanging locker to starboard with LED lighting
- 2 large drawers underneath the berth
- Side bed tables with leatherette
- Fully upholstered front bulkhead
- 2 large storage areas in front of the cabin
- LED lighting
- Opening deck hatch, for light and ventilation
- 2 large fixed hull ports with sliding blinds
- · Deck hatches with blind and bug screens
- · Forward cabin head (versions B and D): En-suite

#### Options

- Mattress battens
- · Large additional dressing on port side and a furniture
- of manual toilets (versions B and D)